

# LEIPA Shine

CEPI-Code 73 Tentative specification

LEIPA Shine is part of our comprehensive range of packaging papers suitable for the corrugated production. It is a double coated white top testliner based on 100% recycled waste paper and designed for great print results in offset printing. LEIPA Shine's homogeneous surface guarantees excellent contrasts.

### Characteristics

- » High brightness
- » Smooth and homogeneous surface
- » High contrast

### Key Benefits

- » Supports the sustainable market for recovered paper
- » It will be developed for the use in offset printing and to print a wider range of colours with excellent print results

Properties	Unit	Standard	Target Figures			Tolerances
Grammage	g/m <sup>2</sup>	ISO 536	160	180	210	± 4%
Moisture	%	ISO 287	6,5	6,5	6,5	± 1,0
Burst resistance	kPa	ISO 2759	305	350	380	- 10%
SCT CD	kN/m	ISO 9895	2,3	2,7	3,2	- 0,3
Cobb60 (top side)	g/m <sup>2</sup>	ISO 535	35	35	35	≤ 50
Brightness (top side)	%	ISO 2470-2	87	87	87	- 1
Roughness PPS (top side)	µm	ISO 8791-4	1,9	2,0	2,5	+ 0,7
Caliper	µm	ISO 534	165	185	215	± 5%

All values are measured under standard climate condition (23°C, 50% RH). Our measurement devices are included within the CEPI cycle.

### Certifications



Are you interested? Please contact us.

[www.leipa.com/packagingpaper](http://www.leipa.com/packagingpaper)  
[sales@leipa.com](mailto:sales@leipa.com)  
 +49 3332 24-3000

